

NEW MUTCD Minimum Maintained Retroreflectivity Levels Quick Reference Guide

(in units of cd/lx/m² measured at an angle of 0.2° and an entrance angle of -4.0°)

Information taken from the FHWA Manual on Uniform Traffic Control Devices for Streets and Highways

Sign Color	Additional Criteria	Sheeting Type			
		Beaded Sheeting			Prismatic Sheeting
		I	II	III	III, IV, VI, VII, VIII, IX, X
White on Green	Overhead	white not approved; green ≥ 7	white not approved; green ≥ 15	white not approved; green ≥ 25	white ≥ 250; green ≥ 25
	Ground-mounted	white not approved; green ≥ 7	white ≥ 120; green ≥ 15		
Black on Yellow or Black on Orange	For text and fine-symbol signs measuring ≥ 1200mm (48in) and all bold symbol signs	yellow/orange not approved	yellow ≥ 50; orange ≥ 50		
	For text and fine symbol signs measuring < 1200mm (48in)	yellow/orange not approved	yellow ≥ 75; orange ≥ 75		
White on Red	Minimum sign contrast ratio ≥ 3:1 (white retroreflectivity / red retroreflectivity)	white ≥ 35; red ≥ 7			
Black on White	—	white ≥ 50			

Are you ready for the new MUTCD Regulations?

The RoadVista 922 Handheld Sign Retroreflectometer



- Most advanced sign retroreflectometer available. Measures all sheetings with a single measurement.
- Meets ASTM, CIE and DIN specifications.
- Easy operation with a LCD touch screen display, built in GPS and Barcode reader.
- Measures in both 0.2 and 0.5 degrees for simultaneous measurements.

Also available for measuring pavement marking retroreflectivity:

StripeMaster II



LaserLux



Manufactured by:
RoadVista
Phone: 858-279-6044
Toll Free: 888-637-2758
Fax: 858-576-9286
www.roadvista.com

ROADVISTA

Distributed in FL, GA, AL, TX, LA, and MS by:
Professional Pavement Products, Inc.
Phone: 904.733.2121
Toll Free: 800.523.6157
Fax: 904.733.8800
www.pppcatalog.com

